Mini Tubular Level Gauge for Liquids - 'MTTG'



It is compact & economical gauge for visual indication of liquid levels in small tanks.

Construction & Operation: Fig 1

Consists of a toughened borosilicate gauge glass tube fitted between two metallic end blocks through a leak proof gland packing system. Guards are provided in the form of 'C' channels, fixed on the end blocks to protect gauge glass from accidental blows. The gauge is side mounted to tank, so as to form a closed loop, causing tank liquid to seek its level in the gauge.



End Blocks : SS304 or SS316 Process Conn : 1/4"BSP (F)

Gauge Glass : Toughened Borosilicate Glass

16 OD x 3mm Thk.

Guards : MS 'C' channel (Epoxy Pdr Ctd)

Gland : MS (Epoxy Pdr Ctd)

Vent & Drain : 1/4"BSP Plug

Gland Packing : Neoprene / Viton O- Ring Calibrated Scale : Polycarbonate (LC=2mm)

CC Dist (Range) : 100, 200, 250, 300, 350 or 400mm

Visibility : V = CC Dist - 55mm

Max. Temperature: 70° C (Neoprene) or 100° C (Viton)

Pressure Rating : 10 Kg/cm² at Amb. Temp

Installation: Fig 2

The gauge is side mounted to the tank through thread fittings, ensuring that it is mounted in plumb. CC distance between tank fittings should correspond to CC dist. of gauge, failing which it may cause gauge glass damage / breakage.

Applications:

Water, Solvents, Acids, Synthetic Oils & Hydrocarbon. Small Storage Tanks, Process /Dosing Tanks, Special Purpose Machines & ETP.

ADAPTOR ADAPTOR SING SON SING SING SON SING SI


Ordering Information:

Model no. along with Liquid and its Optg. Temp & Pressure


 ϵ

Construction

Fig. :



Model Identification



Units in mm

Pune Techtrol Pvt Ltd [CIN: U31909PN1991PTC063403]

Address: S-18, MIDC, Bhosari, Pune - 411026. India

□ ho@punetechtrol.com ② +91-20-66342900 ⑤ www.punetechtrol.com

Works : J-52/7, MIDC, Bhosari, Pune - 411026. India ① +91-20-67313600

Custom built specs./options available on demand.

We reserve the right to modify design and specifications without prior notice.

